

CQC Commercial White 100	Unit	Weight	Total Weight
Commercial Quartz Component Base	12 bags	50 lbs.	600 lbs.
White Portland Cement	4 bags	94 lbs.	376 lbs.
NPT Lobo Modifier / Quartz	1 bag	25 lbs.	25 lbs.
Total Weight			1001 lbs.



CQC Commercial White 50/50	Unit	Weight	Total Weight
Commercial Quartz Component Base	6 bags	50 lbs.	300 lbs.
Marble Aggregate	3 bags	100 lbs.	300 lbs.
White Portland Cement	4 bag	94 lbs.	376 lbs.
NPT Lobo Modifier / Quartz	1 bag	25 lbs.	25 lbs.
Total Weight			1001 lbs.



JPL-37-2567 Commercial Quartz Component

NPT-37-4514 NPT Lobo Modifier / Quartz

To be eligible for limited lifetime warranty coverage

1. An **NPT** Approved Applicator must do the installation
2. NPT Lobo Modifier / Quartz must be used
3. Warranty Registration must be submitted on a Limited Lifetime Warranty form supplied by the Approved Applicator

*Standard Warranty Coverage is 10 years on all QuartzScapes pool finishes

**Commercial Pools included

***Approved Applicators can alter the warranty coverage period to be less than lifetime and more than 10 years.


A new customized warranty form will be created to represent the new time frame.

Technical Guidelines for Plaster Industry (NPC)

Section 3.4

Thickness Tolerance:

The cementitious surface coating should have a minimum thickness of 3/8" and a maximum thickness of 3/4". Though thickness fluctuations exist across the cementitious surface coating, the majority of the cementitious surface coatings' thickness should remain within these tolerance levels. The Cementitious surface coating is not designed to have structural value.



Plaster Coverage Rates

Exposed Quartz = 220 sq. ft. @ 1/2" thickness

1,051 lbs batch = 700 lbs of aggregate + 376 lbs of cement + or-